



ORDER DETAILS

CODE: 85007.2000102
 Colours: 902 Black Sand
 Size: 2MM

TOOLS NEEDED:

- Tap out tool (eg small Allen Key or Phillips head screwdriver)

STEP 1:



Pull the Quick Release Handle up, in the direction of the arrow.

STEP 2:



Locate the knurled locking pin that holds the release pin in place. The locking pin will be marked with a dot on one end. This is the end of the pin you will need to lightly tap to remove the release pin in order to access the small o-ring. Remove the Release Pin from inside the QR Body.

STEP 3:



Remove the Release pin from the QR and locate the O-ring. Remove the old O-ring.

STEP 4:



Take your new O-ring and hook it over the top of the release pin end and stretch it over the hook on the end of the cam part.

STEP 5:



Re-install the release pin inside the QR Body by pushing the knurled locking pin back in place. Ensure each end of Locking Pin is flush with corresponding surfaces on the QR Body.

Note: It's best to push the locking pin (non-knurled end first) back into the QR Body from the side where the knurling was seated,

STEP 6:



Test Quick Release is functioning correctly.



WARNING: Failure to install this product correctly may result in serious bodily injury or death. Please contact your local North Retailer for support and ask for a qualified and experienced repair shop to carry out the repair. If you choose to carry out this repair yourself, please read and understand all steps contained in this installation guide before commencing installation. Take all necessary safety precautions. Safety precautions may include taking extreme care when using sharp objects and wearing all personal protective equipment necessary.